

# MS1200



## Properties

MS1600 is a paste forming homo-polymeric micro-S-PVC that is suitable for producing low viscosity pastes.

## Product specification

Test Items	Method	MS1600
K Value	ISO 1628	77-79
Volatile Matter (%)	ISO 1269	$\leq 0.5$
Bulk Density (ml/g)	ISO 60	0.20-0.45
Whiteness (%)	GB/T 15595	$\geq 80$
Residual VCM (ppm)	ISO 6401	$\leq 5$
Sieve retention(%)	ISO 22498	(250um) $\leq 0$
		(63um) $\leq 0.1$
Paste viscosity(mPa.s)	GB/T 15592-2008	1500-4500
Thickening rate(24h) (%)	GB/T 15592-2008	$\leq 100$

## Application

Pastes based on MS1600 can be applied by all common processing technologies. All these properties make the product suitable for transparent top coats in CV-flooring, artificial leather or dip coating goods such as gloves.

## Packaging



20kg kraft paper packaging。

## Precautions for storage and transportation

Products should be stored in a ventilated and dry place, should keep away from heat/sun/rain/dampness.

Transportation must be carried with a clean awning, to prevent rain. This product is non-dangerous material, can be delivered as normal cargo.

Yunnan Zhengbang Technology Co., Ltd  
Address: No. 8 Road, Haikou Industrial Park, Xishan  
District, Kunming  
Tel: +86-0871-6563 1166  
Fax: +86-0871-6842 3582  
Postcode: 650224

The data and recommendations contained in this product information represent the current state of our knowledge and serve as a guide only to our products and their potential applications. Therefore, no warranty of specific properties of the products mentioned here in nor of their suitability or fitness for a particular purpose is implied. The information given in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also used. Patent or other proprietary rights of third parties must be observed. The quality of our products is warranted under the terms of our General Conditions of Sale.